


## Excel Grade 80 Components

**XLC Self Locking Hooks** are traditional sized hooks with a larger release mechanism making them easier to use with gloves, and are therefore recommended for the construction industry. The clevis enables a direct connection to Grade 80 chains.



### XLC Clevis Self Locking Hook

Code	W.L.L. t	Chain ø mm	Dimensions mm				P	Weight kg
			A	B	C	D		
XLC 0	1.12	5/6	92	16	24	28	32	0.47
XLC 1	2.00	7/8	111	23	29	32	44	0.90
XLC 2	3.15	10	141	30	34	41	49	1.72
XLC 3	5.30	13	167	35	43	53	64	3.21
XLC 4	8.00	16	205	39	57	64	78	5.93
XLC 5	12.50	18/20	234	53	59	80	92	9.10




Safety Factor 4:1

**GH Excavator Hooks** are welded directly to the booms of bucket or crane loaders. (Welding instructions are supplied with each hook). Note: Lifting with the teeth of an excavator is forbidden. Latches are fitted as standard, to prevent accidental unhooking.



### GH Excavator Hook

Code	W.L.L. t	Dimensions mm			Weight kg
		A	B	P	
GH 0.75	0.75	56	70	22	0.23
GH 1	1.00	71	78	25	0.48
GH 2	2.00	91	81	36	0.72
GH 3	3.00	104	104	39	1.07
GH 4	4.00	120	129	42	1.59
GH 5	5.00	136	146	47	2.32
GH 8	8.00	145	146	52	3.27
GH 10	10.00	178	193	77	6.07
GH 15	15.00	185	225	76	9.00



Respect welding instructions.


Safety Factor 4:1

**MJ Chain Connectors** provide fast, easy assembly without the need for special tools or skills. Designed for attaching hooks, master links and other end fittings to Grade 80 alloy steel chains.



### MJ Chain Connector

Code	W.L.L. t	Chain ø mm	Dimensions mm			Weight kg
			A	B	C	
MJ 6	1.12	6	45	40	15	0.14
MJ 7/8	2.00	7/8	54	52	20	0.15
MJ 10	3.15	10	63	65	25	0.32
MJ 13	5.30	13	84	82	30	0.68
MJ 16	8.00	16	104	103	36	1.26
MJ 18/20	12.50	18/20	127	120	45	2.02
MJ 22	15.00	22	155	144	51	3.18
MJ26	21.20	26	160	172	57	4.52
MJ 32	31.50	30/32	174	197	69	8.20



Safety Factor 4:1