


**PP-B**


Bolt-on eye connection  
(swivelling) metric thread



Type	WLL (kgs)	B	C	D (mm)	F	G	M	Weight (kgs/pc.)	Ref. No.
PP-B-0.63t-M12	630	65	35	40	18	41	12	0.35	798 9522
PP-B-1.5t-M16	1500	65	35	46	24	50	16	0.6	798 9523
PP-B-2.5t-M20	2500	75	40	61	30	61	20	1.1	798 9081
PP-B-4t-M24	4000	95	45	78	36	78	24	2.4	798 9082
PP-B-5t-M30	5000	130	60	95	45	93	30	5.2	798 9524
PP-B-8t-M36	8000	140	65	100	54	102	36	6.3	798 9083

**PP-S**

Bolt-on universal connection  
(swivelling) metric thread



Type	WLL (kgs)	B	C	D (mm)	F	G	M	Weight (kgs/pc.)	Ref. No.
PP-S-0.63t-M12	630	75	18	40	18	41	12	0.4	799 0719
PP-S-1.5t-M16	1500	97	25	46	5	50	16	1.0	798 9719
PP-S-2.5t-M20	2500	126	30	61	30	61	20	1.7	798 9075
PP-S-4t-M24	4000	150	35	78	36	77	24	3.5	798 9076
PP-S-5t-M30	5000	174	40	95	45	93	30	7.2	798 9720
PP-S-8t-M36	8000	208	48	100	54	102	36	9.2	798 9077

**VLBG**

Ring bolt  
with Metric coarse thread  
360° rotation



Type	WLL (kgs)	C	H (mm)	T	Weight (kgs/pc.)	Ref. No.
VLBG-0.3t-M8	300	34	11	75	0.40	850 0821
VLBG-0.63t-M10	630	34	16	75	0.40	850 0822
VLBG-1t-M12	1000	34	21	75	0.40	850 0823
VLBG-1.5t-M16	1500	36	24	85	0.50	850 0824
VLBG-2.5t-M20	2500	54	32	110	1.30	850 0826
VLBG-4t-M24	4000	54	37	125	1.50	850 0827
VLBG-4t-M27	4000	65	39	147	3.10	798 3658
VLBG-5t-M30	5000	65	49	147	3.30	850 0828
VLBG-7t-M36	7000	65	52	146	3.40	850 0829
VLBG-8t-M36	8000	82	63	197	5.80	798 3553
VLBG-10t-M42	10000	80	73	162	6.40	798 3554
VLBG-15t-M42	15000	100	63	222	10.7	798 2966
VLBG-20t-M48	20000	100	73	222	11.1	798 2967

**RBG/VRBG**


Eye plate Bolt on



Type	WLL (kgs)	D (mm)	L	Bolt Size	Weight (kgs/pc.)	Ref. No.
RBG-3	3200	48	178	M16 x 50	0.90	51817
RBG-8	8000	65	194	M20 x 70	3.80	59971
VRBG-16	16000	90	270	M30 x 90	7.8	799 3255
VRBG-30	30000	130	400	M30 x 100	67	798 5866
VRBG-50	50000	230	650	M36 x 120	210	798 5867

**VRM Starpoint**


Eyebolt with Metric coarse thread  
360° Rotation



Type	WLL F1 (kgs)	WLL F2 (kgs)	D (mm)	K	L	Weight (kgs/pc.)	Ref. No.
VRM-M8	1000	400	25	47	12	0.10	799 2989
VRM-M10	1000	400	25	47	15	0.10	799 0311
VRM-M12	2000	750	30	56	18	0.20	799 0312
VRM-M16	4000	1500	35	65	24	0.30	799 0314
VRM-M20	6000	2300	40	75	30	0.50	799 0315
VRM-M24	8000	3200	48	90	36	0.90	799 0316
VRM-M30	12000	4500	60	112	45	0.70	799 3008

**RS**


Eyebolt  
Metric coarse thread  
High tensile



Type	WLL F1 (kgs)	WLL F2 (kgs)	C (mm)	D	Weight (kgs/pc.)	Ref. No.
RS-M6	400	100	12	25	0.10	61401
RS-M8	800	200	12	25	0.10	61402
RS-M10	1000	250	15	25	0.12	56397
RS-M12	1600	400	18	30	0.18	56398
RS-M14	3000	750	21	35	0.30	56403
RS-M16	4000	1000	24	35	0.30	56404
RS-M20	6000	1500	30	40	0.47	56407
RS-M24	8000	2000	36	50	0.89	56408
RS-M30	12000	3000	45	60	1.57	56409
RS-M36	16000	4000	54	90	6.20	56954
RS-M42	24000	6000	63	90	6.40	56955
RS-M48	32000	8000	68	90	6.60	56956

**VRS-F Starpoint**

Eyebolt with Metric coarse thread  
360° Rotation



Type	WLL F1 (kgs)	WLL F2 (kgs)	D (mm)	K	L	Weight (kgs/pc.)	Ref. No.
VRS-F-M8	1000	400	25	47	15	0.10	850 0911
VRS-F-M10	1000	400	25	47	15	0.12	710 4029
VRS-F-M12	2000	750	30	56	18	0.18	710 1313
VRS-F-M16	4000	1500	35	65	24	0.32	710 1314
VRS-F-M20	6000	2300	40	75	30	0.51	710 1315
VRS-F-M24	8000	3200	48	90	36	0.92	710 1316
VRS-F-M30	12000	4500	60	112	45	1.80	710 1317
VRS-F-M36	16000	7000	72	135	54	3.35	798 4201
VRS-F-M42	24000	9000	82	158	63	5.14	798 4202
VRS-F-M48	32000	12000	94	180	72	7.80	798 4203



**SYDNEY**  
Phone: (02) 9531 8033  
Fax: (02) 9531 7933  
Email: sales@hesnsw.com.au  
www.hesnsw.com.au

**MELBOURNE**  
Phone: (03) 9480 5577  
Fax: (03) 9480 0855  
Email: sales@hesvic.com.au  
www.hesvic.com.au

**ADELAIDE**  
Phone: (08) 8244 7611  
Fax: (08) 8244 7699  
Email: sales@schillings.com.au  
www.schillings.com.au

**PERTH**  
Phone: (08) 9355 4218  
Fax: (08) 9472 7970  
Email: sales@heswa.com.au  
www.heswa.com.au

