



WBG-V

Swivel ring bolt
Metric coarse pitch 360° rotation
Standard (F*) and variable (Fvario) bolt
lengths available



Type	WLL (kgs)	A	C (mm)	F*	Weight (kgs/pc.)	Ref. No.
WBG-V-0.3 M8	300	8	29	12	0.17	710 3720
WBG-V-0.45 M10	450	8	29	15	0.19	710 3715
WBG-V-0.6 M12	600	10	35	21	0.38	710 0180
WBG-V-1.3 M16	1300	10	35	30	0.56	710 0430
WBG-V-2.0 M20	2000	13	35	33	1.28	710 0800
WBG-V-3.5 M24	3500	18	40	40	2.66	710 0640
WBG-V-5.0 M30	5000	22	50	50	5.00	710 0650








Grade 100 Alloy Chain - RUD

The most technologically advanced alloy sling chain system available - with 25% higher working load capacity and greater wear resistance than Grade 80 (T) chain. This system comes with an extensive range of fittings, to offer the most innovative chain sling system available.

VIP - Special Quality

For single and multiple strand sling chains with different angles of inclination for symmetrical loading of the strands.

Available in sizes 4mm through to 22mm. Every chain link is stamped with the VIP logo. Serial and batch numbers are stamped every running metre. A highly visible colour which discolours under high temperatures and a dual process surface coating for increased corrosion resistance.

RUD – Lifting Systems in Special Quality		single leg slings		slings of 2, 3 or 4 legs		
						
	Grade 100	Straight sling	Reeved sling	Straight sling		
	Chain dia.			60°	90°	120°
	VIP 4	0.63	0.47	1.1	0.89	0.63
	VIP 6	1.5	1.1	2.6	2.1	1.5
	VIP 8	2.5	1.9	4.3	3.5	2.5
	VIP 10	4.0	3.0	6.9	5.6	4.0
	VIP 13	6.7	5.0	11.6	9.4	6.7
	VIP 16	10.0	7.5	17.3	14.1	10.0
	VIP 20	16.0	12.0	27.8	22.7	16.0
	VIP 22	20.0	15.0	34.6	28.2	20.0
		Temperature °C			-10 < to + 200	
		Deration			none	



SYDNEY
Phone: (02) 9531 8033
Fax: (02) 9531 7933
Email: sales@hesnsw.com.au
www.hesnsw.com.au

MELBOURNE
Phone: (03) 9480 5577
Fax: (03) 9480 0855
Email: sales@hesvic.com.au
www.hesvic.com.au


ADELAIDE
Phone: (08) 8244 7611
Fax: (08) 8244 7699
Email: sales@schillings.com.au
www.schillings.com.au

PERTH
Phone: (08) 9355 4218
Fax: (08) 9472 7970
Email: sales@heswa.com.au
www.heswa.com.au



WBG

Swivel ring bolt
Heavy duty Metric coarse pitch 360° rotation




Type	WLL (kgs)	A	C (mm)	F	Weight (kgs/pc.)	Ref. No.
WBG-8 M36	8000	22	50	54	4.75	51872
WBG-10 M42	10000	26	65	63	6.4	51874
WBG-10 M48	10000	26	65	68	6.6	51930
WBG-15 M56	15000	32	70	84	11.2	51941
WBG-15 M64	15000	32	70	96	11.5	710 0406
WBG-35 M90	35000	40	80	135	13.6	798 5363



VABH-B

Excavator Hook bolt-on
Extremely robust forged safety latch
Non-protruding tip of the hook



Type	WLL (kgs)	B	C	F (mm)	G	H	Weight (kgs/pc.)	Ref. No.
VABH-B-1.5t	1500	78	117	70	48	60	0.78	850 2194
VABH-B-2.5t	2500	101	148	85	60	75	1.73	850 2143
VABH-B-4t	4000	122	171	104	70	90	3.0	850 2221
VABH-B-6.7t	6700	156	208	120	85	110	5.6	850 2238

VIP Overheating Indication

This special fluorescent pink powder coating permanently changes colour at increased temperatures. Colour black signifies an application at more than 400°C (715°F). Further use is then prohibited.



Due to a special heat treatment developed by RUD, the high-dynamic VIP chains are more resistant to external mechanical wear friction and damage. Therefore, longer service life is guaranteed.

All RUD-VIP chains and components are electromagnetically crack detected to ensure greater safety.

WLL in tonnes