

Pacific Hand Winches

The cost-effective solution for a wide variety of applications, Pacific Load Brake Hand Winches can be used to pull or lift loads.

FEATURES

- Positive action brake can hold the load in any position
- Compact, light weight and rugged construction
- Mechanical components enclosed for protection
- Baked enamel finish for corrosion protection
- Rope to drum fixing clamp provided
- Available in corrosion resistant grade 304 stainless steel
- 'Noiseless' model available in BHW range



COMPLIES WITH AS1418.2

Model	BHW-800	BHW-1200	BHW-1800	BHW-2600	SF-2200	HW-1500
Capacity (kg) Pull - Lift	370 - 180	545 - 270	820 - 410	1200 - 600	1100	680
Hand force required kg	14.5	15	22	19	16	4.5
Gear ratio	4.1:1	4.1:1	5:1	10:1	22.2:1	41:1
Hub diameter mm	ø40	ø50	ø70	ø80	ø60	ø48
Handle length mm	160	210	320	320	300	195
Unit weight kg	3	3.3	8	10.3	13.5	4.9
Rope diameter mm	ø4	ø5	ø7	ø8	ø8	ø4
Rope storage capacity m	36	23	24	18	35	23

AS1418.2 Standard applies when fitted with approved wire rope and fittings.



Gears are strong, durable and electroplated for extra corrosion resistance.



Double brake pawl for extra safety on BHW-1800 and BHW-2600 models

Model SF-2200

Ideal for use in confined locations, the ratchet handle permits reciprocating handle movement in both directions for hoisting and lowering loads.

