

Commercial Chain

Proof coil chain - self colour or galvanised for general purpose applications
NOT TO BE USED FOR LIFTING

Regular Link Proof Coil Chain



Approx. Size mm	M.W.L. in tonnes
3	0.07
4	0.10
5	0.20
6	0.30
8	0.50
10	0.80
13	1.50
16	2.30
20	3.67
24	5.34

Short Link Proof Coil Chain



Approx. Size mm	M.W.L. in tonnes
6	0.30
8	0.50
10	0.80
13	1.50
16	2.30


Long Link Proof Coil Chain



Approx. Size mm	M.W.L. in tonnes
5	0.20
6	0.30
8	0.50
10	0.80

Grade L Anchor Chain

Manufactured in a short link configuration meeting the requirements of Australian Standard AS2321, Grade L Chain is the highest quality lower tensile steel available for lifting purposes and recommended for most marine and mooring applications.



Chain Size mm	W.L.L. tonnes	S mm	R mm	F mm	Self-colour metres/100kg	Galvanised metres/100kg
6	0.40	6.3	18.8	21.6	116.0	110.0
8	0.64	8.0	23.8	27.0	71.4	67.8
10	1.00	10.0	29.8	34.3	45.5	43.2
13	1.70	12.7	38.0	43.0	29.6	27.8
16	2.58	16.0	47.8	54.9	17.8	17.5
20	4.03	20.0	59.2	68.5	11.3	11.1
22	5.06	22.0	64.9	77.0	9.5	9.2

